

Medida del Neumático			Protección Severa (litros)	Protección Total (litros)
Ancho	Aro		Severa	Total
7,00	-	15,0	1,00	3,00
8,25	-	15,0	1,00	5,00
6,50	-	16,0	1,00	3,00
7,00	-	16,0	1,00	3,00
7,50	-	16,0	1,00	4,00
7,50	-	17,0	1,50	4,00
8,50	-	17,5	1,50	6,00
9,00	-	17,5	1,50	7,00
9,00	-	20,0	1,50	8,00
10,00	-	20,0	4,00	10,00
11,00	-	20,0	4,00	14,00
12,00	-	20,0	4,00	17,00
11,00	-	22,0	4,00	15,00
10,00	-	22,5	4,00	11,00
11,00	-	22,5	4,00	15,00
12,00	-	22,5	4,00	19,00
13,00	-	22,5	6,00	24,00
12,00	-	24,0	8,00	20,00
14,00	-	24,0	8,00	30,00
16,00	-	24,0	8,00	43,00
18,00	-	33,0	24,00	74,00

Ancho	Perfil	Aro		Severa	Total
205	/	70	R 15,0	1,0	3,00
225	/	70	R 15,0	1,0	4,00
195	/	75	R 16,0	1,0	3,00
225	/	75	R 16,0	1,0	5,00
265	/	75	R 16,0	1,5	8,00
205	/	75	R 17,5	1,5	4,00
215	/	75	R 17,5	1,5	5,00
215	/	80	R 17,5	1,5	5,00
235	/	75	R 17,5	1,5	6,00
275	/	70	R 22,5	4,0	10,00
275	/	80	R 22,5	4,0	13,00
295	/	80	R 22,5	4,0	16,00
310	/	80	R 22,5	4,0	18,00
315	/	80	R 22,5	4,0	19,00
385	/	55	R 22,5 Super Single	6,0	18,00
385	/	65	R 22,5 Super Single	6,0	23,00
425	/	65	R 22,5 Super Single	6,0	30,00
445	/	65	R 22,5 Super Single	6,0	34,00
325	/	95	R 24,0	8,0	28,00
305	/	75	R 24,5	8,0	17,00



SEVERA: Protección de la Banda de Rodamiento y parte del hombro del Neumático.

TOTAL: Protección hasta el Talón del Neumático.